


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61F 2/38	A1	(11) International Publication Number: WO 94/09725 (43) International Publication Date: 11 May 1994 (11.05.94)
<p>(21) International Application Number: PCT/US93/10188</p> <p>(22) International Filing Date: 25 October 1993 (25.10.93)</p> <p>(30) Priority data: 07/969,129 30 October 1992 (30.10.92) US</p> <p>(71) Applicant: ENCORE ORTHOPEDICS, INC. [US/US]; 8920 Business Park Drive, Suite 380, Austin, TX 78759 (US).</p> <p>(72) Inventors: TURANYI, Sandor ; P.O. Box 134, Red Rock, TX 78662 (US). JONES, Robert ; 9505 Union Circle, Austin, TX 78744 (US). WEBB, John, D. ; 1001 Oakwood Boulevard, Round Rock, TX 78684 (US).</p>		<p>(74) Agents: TANNENBAUM, David, H. et al.; Winstead Sechrest & Minick, 5400 Renaissance Tower, 1201 Elm Street, Dallas, TX 75270 (US).</p> <p>(81) Designated States: CA, FI, JP, KR, NO, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: PROSTHESIS SYSTEM



(57) Abstract

A tibial insert and baseplate system is disclosed for a prosthesis. The tibial baseplate is right or left knee specific while the insert is symmetrical about an anterior-posterior centerline and is thus not right or left knee specific. The baseplate has an outer periphery which is asymmetrical to mate exactly with either the left or right tibia but not with both. The upper surface of the baseplate, which also has an asymmetrical periphery, in addition, defines a symmetrical housing within the periphery for the symmetrical insert.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LJ	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

PROSTHESIS SYSTEM

TECHNICAL FIELD OF THE INVENTION

This invention relates to orthopedic prostheses,
and more particularly to prostheses utilized in joint
5 replacements.

BACKGROUND OF THE INVENTION

There is a well known fact that the joints of humans as well as animals deteriorate over time. Sometimes deterioration occurs because of disease due to aging and sometimes due to a trauma. The knee joint is perhaps the one joint that has given people the most trouble over the years because of its essential function to the mobility of humans. Thus, quite naturally, a great deal of research has gone into the development of replacement knees. Today, because of this widespread research, a significant portion of our population is again mobile and relatively free of pain. This great step forward in medical research has not been without its difficulties. Primarily because of the tremendous stresses placed on the knee joint, there continues to be a need for improvement to eliminate the last vestiges of pain and suffering.

Prosthetic surgery involving the excision and removal of deteriorated and diseased bone tissue in knee and hip joints has now become quite common. Typically, artificial members of plastic and/or metal compatible with the human body are substituted for the removed natural bone segments and anchored to the remaining bone structure.

The bearing surfaces of the knee joint are especially vulnerable to stress, arthritic and other disease induced deterioration. Prosthetic correction is necessary when the surfaces become so damaged that other less drastic techniques have little or no prospect of success.

In a healthy knee, the lower leg bone, called the tibia, has at its upper end a pair of concave surfaces.

These concave surfaces meet with condyles which are formed in the lower end of the femur, which is the upper leg bone. This meeting is protected by the patella (knee cap). Thus, in a knee replacement operation, the upper end of the tibia is removed as is the lower end of the femur, and these bones are replaced with prostheses, which are designed to operate together.

In the past, there have been two major types of knee prostheses: hinged and non-hinged. In one form, the knee was resected and replaced by a metal hinged-type device with deep penetration into the remaining femoral and tibial bone structure by means of flared and thick stems. The range of movement was limited and patients were seldom able to flex the knee beyond 90°. Moreover, implantation required the removal of a significant amount of the bone with a shortening of the limb if for any reason the prosthesis was later removed.

More recent prostheses using a different approach attempt to structurally resurface both of the articulating surfaces of the knee to provide a non-hinged type prosthesis. Such prostheses seek to remedy the failure of hinged devices, and involve two components which are respectively connected with the femur and tibia and held in engagement by the muscles and ligaments to produce a more lifelike situation.

The non-hinged knee prostheses must contend with the particulars of the human knee joint. The tibia is situated at the front (anterior) and inner (medial) side of the lower leg and, except for the femur, is the longest and largest bone in the human skeleton. It is prismoid in form, expanded above, where it enters into

the knee joint. The head of the tibia is large and expanded on each side into two eminences called the tuberosities. The tops of these present two smooth concave surfaces which articulate within the knee with the condyles of the femur. The medial condyle is more prominent anteriorly and broader both in the anterior-posterior (front-rear) and transverse diameters than is the outside (lateral) condyle. Accordingly, the lateral top articular surface of the tibia is longer, deeper and narrower than the medial surface of the tibia so as to articulate with the lateral condyle. The medial surface is broader and more circular, concave from side to side, to articulate with the medial condyle. The anterior surfaces of the tuberosities are continuous with one another, forming a single large surface which is somewhat flattened. Posteriorly the tuberosities are separated from each other by a shallow depression for attachment of ligaments. The inner (medial) tuberosity presents posteriorly a deep transverse groove for the insertion of the posterior cruciate ligament (PCL).

In the past, tibial prostheses (commonly called baseplates because they fit beneath the condyles of the femur) were manufactured with total symmetry for use with both left and right knees which, as was discussed above, are not symmetrical. Although the symmetrical components were interchangeable between the right or left tibia, there were problems with the baseplate overhanging the lateral tibial bone surface or undersized on the medial tibial bone surface. The result was a compromise in the fit of the prosthesis. In response thereto, asymmetric tibial prostheses (baseplates) were developed to more closely approximate the natural tibial anatomy. The problem with such

asymmetric tibial prostheses is that they require asymmetric, or knee specific removable tibial baseplate inserts (the concave bearing surface which actually contacts the femoral condyles) necessitating the need
5 for a hospital to maintain an inventory of left and right knee specific inserts.

U.S. Patent No. 4,963,152 provides a partial solution to the problems associated with symmetrical tibial prostheses. The patent discloses an
10 asymmetrical tibial prosthesis whereby asymmetry is created by having the outer radius which describes the medial condyle slightly greater than the outer radius describing the lateral condyle. However, the baseplate is symmetrical about the medial-lateral centerline,
15 allowing it to be used on either left or right tibia by rotating the baseplate 180° about the centerline. The insert, which is designed to mate with the baseplate, is also symmetrical about the medial-lateral centerline. The disadvantage of such a tibial
20 prosthesis is that it must include an anterior as well as a posterior relief notch for the PCL in order to allow the baseplate to be reversed and thus usable on either the left or right knee. The "extra" notch, along with the symmetrical geometry of the baseplate
25 about the medial-lateral centerline, does not provide the best coverage of the prosthesis upon the head of the tibia.

In order to provide the best coverage, the baseplate should be formed with only one notch for the
30 PCL and thus cannot be symmetrical about either the medial-lateral centerline or the anterior-posterior centerline. However, such a baseplate would require a correspondingly asymmetrical insert under the teachings of the prior art.

Since these inserts may wear out and require replacement prior to the tibial baseplate, it becomes more costly from an administrative standpoint to maintain an inventory of both left and right knee
5 inserts.

What is needed is a low cost symmetrical tibial insert that can be mass-produced so as to lower inventory and replacement costs and which is still usable in conjunction with an asymmetric tibial
10 baseplate.

The object of the present invention is to provide a knee prosthesis having a tibial baseplate specific to the left or right tibia but allowing for the placement of an insert which is symmetrical about its
15 anterior-posterior centerline and thus not left or right knee specific. The knee prosthesis also includes a femoral component having condyles for articulating with the condyle compartments of the symmetrical insert.

SUMMARY OF THE INVENTION

The present invention is for a knee replacement prosthesis comprising a baseplate having a medial end with a first arcuate outer perimeter and a lateral end with a second arcuate outer perimeter. The first arcuate outer perimeter has a radius of curvature greater than the radius of curvature associated with the second arcuate outer perimeter. The baseplate also has a means for receiving an insert on the upper surface of the baseplate, this means including arcuate peripheral ledges having equal radii circumscribed on the baseplate within the outer unequal radii. The insert has a medial condyle compartment and a lateral condyle compartment for articulating with femoral condyles of a femoral component. Each compartment has arcuate outer perimeters of equal radius for positioning in juxtaposition with the peripheral ledges of the baseplate.

The baseplate, insert and femoral component each include a notch between the medial end and the lateral end behind the medial-lateral centerline to allow for the PCL.

The baseplate is connectable to a human tibia and the femoral component is connectable to a human femur.

The baseplate further includes overhangs on the ledges along with at least one recessed lip for receiving a flexible latch attached to the underside of the insert for locking the insert to the baseplate. The baseplate also includes means for securing the baseplate to a resected surface of a patient's tibia. This means could include, if desired, a post which is received into a hole drilled into the head of the tibia

whereby the post is bonded into the hole. Also, a hole within the tibial baseplate could be included, if desired, to allow for the baseplate to be attached to the resected head of the tibia with a bone screw.

5 The baseplate has a substantially elliptical circumference with the medial end having a radius different from the radius of the lateral end so that the baseplate precisely fits upon the resected surface of the tibia for the left and right knees. This
10 eliminates an overhang of the baseplate beyond the circumference of the resected portion of the tibia resulting in a better fit of the tibial baseplate onto the tibia. The asymmetrical baseplate is configured to receive a symmetrical insert onto its upper surface.
15 Thus, any one insert may be mounted to a left or right knee specific baseplate. The insert is configured with substantially similar medial and lateral condyle compartments for articulation with the femoral condyles of a femoral component when the total prosthesis is
20 implanted within the knee.

 The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood.
25 Additional features and advantages of the invention will be described hereinafter which form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and the specific embodiment disclosed may be readily utilized
30 as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not

depart from the spirit and scope of the invention as set forth in the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, and the advantages thereof, reference is now made to the following descriptions taken in conjunction
5 with the accompanying drawings, in which:

FIGURE 1 illustrates an exploded view of a total knee replacement including a femoral component, a tibial baseplate and a corresponding tibial insert;

FIGURE 2 illustrates a top view of the tibial
10 insert;

FIGURE 3 illustrates a bottom view of the tibial insert;

FIGURE 4 illustrates a cross-sectional view of the tibial insert of FIGURE 2 along section lines 4-4;

15 FIGURE 5 illustrates a cross-sectional view of the tibial insert of FIGURE 2 along section lines 5-5;

FIGURE 6 illustrates a cross-sectional view of the tibial insert of FIGURE 2 along section lines 6-6;

FIGURE 7 illustrates a detail of a locking
20 mechanism for securing the tibial insert to the tibial baseplate;

FIGURE 8 illustrates a top view of a tibial baseplate for implant in a right knee;

FIGURE 9 illustrates a bottom view of the tibial
25 baseplate for implant in a right knee; and

FIGURE 10 illustrates a cross-sectional view of an assembled tibial baseplate and insert utilizing the cross-sectional view of the insert in FIG. 5.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. 1, there is shown knee replacement 10 observed from behind the right knee which generally consists of femoral component 11 having medial condyle 14 and lateral condyle 15. Femoral component 11 is attached to femur 16 by the surgeon and operates in conjunction with tibial baseplate 13 attached to tibia 17 and insert 12 mounted to baseplate 13.

10 The superior insert surface, shown in FIGS. 1 and 2, is divided into three areas, medial condyle compartment 20, tibial eminence 40, and lateral condyle compartment 21. Condyle compartments 20 and 21 have substantially similar concave geometries and form the articulating surface for medial condyle 14 and lateral condyle 15 of femoral component 11. Since condyle compartments 20 and 21 are substantially identical and insert 12 is symmetrical about the anterior-posterior centerline (shown in FIG. 3), the terms "medial" and "lateral" are meaningful only after insert 12 is actually placed in a knee. Before placement of insert 12 into a knee, the two terms are completely interchangeable. This can be visualized if one were to imagine a left knee with a knee replacement positioned to the left of knee replacement 10. Such a left knee replacement would have a baseplate (similar to baseplate 13) (not shown) with its wider medial radius facing right while the wider medial radius of baseplate 13 faces left. The left and right baseplates are mirror images resulting in the medial end of each baseplate having a larger radius than the lateral end.

Refer next to FIG. 5, which is cross-section 5-5 of medial condyle compartment 20 of FIG. 2, and

includes both an anterior lip 50 and a posterior lip 51 to limit anterior and posterior motion. Lateral condyle compartment 21 is similarly designed as medial condyle compartment 20. The contouring of condyle
5 compartments 20 and 21 allows for normal internal and external rotation of the articulating couple and also allows for anterior-posterior and medial-lateral movement.

Referring to FIG. 2, the central portion of tibial
10 eminence 40 supplies medial-lateral stability. Posterior portion 22 of insert 12 is notched to allow clearance for the PCL (not shown) when mated with tibial baseplate 13.

As shown in FIGS. 3-6, inferior insert surface 30
15 of insert 12 is flat, with indented edge 41 around its outer periphery. Edge 41 allows insert 12 to nest into the recess on the superior side of baseplate 13. Symmetrical insert 12 is locked into baseplate 13 by means of medial and lateral posterior "L" shaped
20 protrusions 52 (shown in FIG. 5) which fit under overhangs 88 and 89 in baseplate 13, shown in FIG. 8. As illustrated in FIGS. 1, 3, 5-8 and 10, three anterior snap-locks 70, 71 and 72 are engaged into notch 80 on baseplate 13 with an inferiorly-directed
25 force. Of course, any type of locking device could be used, including cement.

Referring to FIG. 6, passageway 60 is formed within tibial eminence 40 to allow insertion of a screw (not shown) to allow for an additional attachment of
30 insert 12 to baseplate 13 whereby the screw is fastened to hole 81 in baseplate 13.

Insert 12 is preferably formed of an ultra-high molecular weight polyethylene (UHMWpe) in pure or fiber reinforced form produced by injection molding, compression molding or machining from bar or slab stock. Other biocompatible, low friction materials having a low wear rate, which can be shaped by molding or machining, could also be used.

Insert 12 (FIG. 2) is symmetrical about the anterior-posterior centerline (shown in FIG. 3) with only one notch 22 for the PCL. An advantage is ease of manufacture resulting in lower manufacturing and inventory costs for inserts that must be replaced due to wear and tear since insert 12 of the present invention is manufactured for use on both the right and left knees. In the present invention, the tolerances and geometries of medial and lateral condyles 20, 21 are substantially similar and are not dependent upon whether insert 12 is placed in the right or left knee. The manufacture of one common symmetrical insert allows the hospital to reduce its required inventory of inserts and relieves the physician of one more decision on whether or not the insert being placed in the tibial baseplate is the correct one for that particular knee.

Turning now to FIGS. 8 and 9, there is shown baseplate 13 which is implanted by the surgeon onto the resected head of tibia 17 (see FIG. 1). This implant can be attached in any one of a number of ways including gluing to tibia 17. One way would be for the surgeon to drill holes into the resected head of tibia 17 and to insert pegs 90, 91, 92 and 93 into the tibia holes as shown in FIG. 1. The surgeon could also, if desired, place screws through holes 83 and 84 of baseplate 13 into tibia 17. In any event, baseplate 13 is permanently mounted to tibia 17.

As shown in FIG. 10, insert 12 is then snapped into baseplate 13 such that "L" shaped protrusions 52 shown in FIG. 5 of the posterior side of insert 12 slip into overhangs 88 and 89. Then snap-locks 70, 71 and 72 of insert 12, which are located on the anterior side of insert 12, are snapped into notch 80, thereby locking insert 12 to baseplate 13.

It is important to note that insert 12, as has been discussed previously, is symmetrical about the anterior-posterior centerline such that the radius of curvature of the periphery of insert 12 measured from points within condyle 21 and condyle 20 is the same. Also note that as shown in FIG. 8, the radius of curvature of the medial circumference of outer periphery 86 of right knee baseplate 13 is R_1 , while the radius of curvature of the lateral circumference of outer periphery 87 of baseplate 13 is R_3 , and that R_1 is greater than R_3 so as to accommodate the physical structure of tibia 17 of the right knee, as discussed previously, such that medial radius of curvature R_1 is greater than lateral radius of curvature R_3 . This allows baseplate 13 to fit coextensively on tibia 17 of the right knee so that there is no overhang or underhang, thereby more evenly distributing the load, thus reducing the occurrence of soft tissue rubbing on the overhang or the baseplate sinking into tibia if it is undersized. Note that the baseplate for the left knee would be the mirror image about the anterior-posterior centerline such that R_3 would be longer than R_1 .

These differences in radius of curvature between R_1 and R_3 give rise to the fact that the surgeon must use a left baseplate and a right baseplate which are not symmetrical about the medial-lateral centerline and

thus cannot be "reversed" thereby requiring two different baseplates. However, because the internal radii R2 of baseplate 13 for both left and right baseplate inserts are identical, insert 12 can be used
5 in either the right or left baseplate. This then allows for only one kind of insert in inventory and allows for insert 12, as discussed above, to be symmetrical about its anterior-posterior axis.

As shown in FIGS. 8 and 9, the posterior section
10 of baseplate 13 contains groove 85 for allowing the patient's PCL to pass therethrough.

Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can
15 be made herein without departing from the spirit and scope of the invention as defined by the appended claims.

WHAT IS CLAIMED IS:

1. A baseplate for a prosthesis comprising:
a medial end with a first arcuate outer perimeter
having a first radius of curvature;
5 a lateral end with a second arcuate outer
perimeter, said first radius of curvature greater than
said second radius of curvature; and
means, including arcuate peripheral ledges
circumscribed on said baseplate, said ledges having
10 equal radii, for receiving an insert on an upper
surface of said baseplate, said insert having a medial
condyle compartment and a lateral condyle compartment
for articulating with femoral condyles, each
compartment having arcuate outer perimeters of equal
15 radius for positioning in juxtaposition with said
arcuate peripheral ledges.
2. The baseplate in claim 1 further comprising:
a single notch between said medial end and said
lateral end, said notch being behind a medial-lateral
20 centerline.
3. The baseplate in claim 1 further comprising:
means, including overhangs on said ledges, for
locking said insert to said baseplate.
4. The baseplate in claim 3 wherein said locking
25 means further includes at least one recessed lip for
receiving a flexible latch attached to an underside of
said insert.
5. The baseplate in claim 2 further comprising:
means, including overhangs positioned on either
30 side of said notch, for locking said insert to said
baseplate.

6. The baseplate as recited in claim 1 further comprising:

means for securing said baseplate to a resected surface on a patient's tibia.

5 7. An implantable plate, mating with an end of a first bone, for supporting a detachable insert, said insert having at least one condyle compartment for mating with at least one condyle at an end of a second bone, said condyle and said insert adapted for
10 controlling articulation between said first and second bones when in mated relationship, said end of said first bone having an asymmetrical circumference with respect to its medial and lateral edges, said plate comprising:

15 means on a bottom surface thereof for attachment to said first bone, said bottom surface being an ellipse with differing circumferences with respect to its medial and lateral ends so as to mate coextensively with said end of said first bone; and

20 a top surface having a circumferential lip at its periphery thereof and extending upward from said top surface, said lip having a width which varies such that an outside periphery of said lip is asymmetrical and identical with the circumferences of said bottom
25 surface and such that an inner periphery of said lip is symmetrical about both an anterior-posterior centerline and a medial-lateral centerline, said lip defining a support area for said insert.

8. The implantable plate in claim 7 further
30 including a single notch between said medial and lateral ends located behind said medial-lateral centerline.

9. The implantable plate in claim 7 further comprising:

means, including overhangs on said ledges, for locking said insert to said plate.

5 10. The implantable plate in claim 9 wherein said locking means further includes at least one recessed lip for receiving a flexible latch attached to an underside of said insert.

10 11. The implantable plate in claim 8 further comprising:

means, including overhangs positioned on either side of said notch, for locking said insert to said plate.

15 12. The implantable plate as recited in claim 7 further comprising:

means for securing said plate to a resected surface on a patient's tibia.

13. A knee implant insert for use between condyles of a femur and a baseplate attached to a
20 tibia, said implant operative to facilitate articulation between said condyles and said tibial baseplate, said tibial baseplate having a flat surface for mating in locking relationship with said insert and having a generally elliptical shaped outer edge with
25 unequal radii of said baseplate's medial and lateral ends and having defined within said outer edge a second generally elliptical shape, said second shape having equal radii of said medial and lateral ends, said insert comprising a pair of concave compartments each
30 substantially identical to the other in size and shape, one of said compartments adapted to mate with a medial condyle of said femur while the other of said

compartments is adapted to mate with a lateral condyle of said femur.

14. The insert set forth in claim 13 further including a convex eminence separating said
5 compartments along an anterior-posterior centerline, sides of said eminence forming at least one side of each of said compartments.

15. The insert set forth in claim 14 wherein said insert further includes:
10 a ligament notch distributed symmetrically about said anterior-posterior centerline and located behind a medial-lateral centerline.

16. The insert set forth in claim 13 wherein said condyles of said femur are implanted at an end of said
15 femur.

17. The insert set forth in claim 13 further comprising:
means, including a flexible latch, removably for locking said insert to said baseplate.

18. The insert according to claim 13 is formed of
20 an ultra-high molecular weight polyethylene.

19. The insert according to claim 13 further comprising:
a posterior central area notch to allow clearance
25 for a posterior cruciate ligament.

1/3









FIG. 1

2/3



3/3

FIG. 7




FIG. 8




FIG. 9





FIG. 10



A. CLASSIFICATION OF SUBJECT MATTER
IPC 5 A61F2/38

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 5 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,4 963 152 (HOFMANN ET AL.) 16 October 1990 cited in the application see the whole document ---	1,3-7, 9-19
A	US,A,4 795 468 (HODOREK ET AL.) 3 January 1989 see column 5, line 64 - column 6, line 18; figures 4-8 ---	1,7,13
A	EP,A,0 495 340 (SULZER AG) 22 July 1992 see abstract; figures -----	2-6, 8-12, 14-19

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

17 March 1994

Date of mailing of the international search report

28.03.94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Villeneuve, J-M

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-4963152	16-10-90	CA-A- 1320315	20-07-93
US-A-4795468	03-01-89	AU-A- 2740888	29-06-89
		DE-A- 3836486	13-07-89
		FR-A- 2625095	30-06-89
		GB-A, B 2214225	31-08-89
		JP-A- 1171543	06-07-89
EP-A-0495340	22-07-92	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.